

MVDS-070-BCSDI

7" LCD BROADCAST MONITOR 3G-SDI, HDMI, YUV and CVBS inputs

PRODUCT DESCRIPTION

MVDS-070-BCSDI is a broadcast LCD monitor for on site monitoring applications. Its IPS LED faceplate gives a high quality display with large view angles. It has a 1280x800 native resolution, but is able to support 1920x1080 full HD.

MAIN FEATURES

- LED IPS wide faceplate
- HDMI, 3G-SDI, YUV and CVBS inputs + Tally
- Good contrast, brightness and view angles
- Advanced functions: 5D II camera mode, Zoom-in, Pixel-to-Pixel, Image flip, Check field, Tally, Center and screen markers, H/V delay, Image freeze, Underscan/overscan
- Delivered with 1x sunshield cover, 1x suitcase, 2x battery adaptors QM91D and DU21, 1x HDMI cable, 1x power supply, 1x support, 1x Tally connector



SPECIFICATIONS

Screen	7" (17.78 cm)
Resolution	1280x800 (support 1920 x 1080)
Brightness	400 cd/m ²
Contrast ratio	800:1
View angles	178°H, 178°V
Inputs	1x CVBS on BNC f. 1x YUV on 3 BNC f. 2x HDMI on HDMI f. 1x 3G-SDI on BNC f. 1x Stereo audio on RCA f.
Outputs	1x HDMI on HDMI f. 1x 3G-SDI on BNC f. 1x audio jack on front
Power supply	7-24V external XLR
Consumption	11 Watt
Dimensions (W x H x D)	191 x 152 x 31 mm (D: 141 with cover)
Weight	0.76 Kg (0.94 Kg with cover)